

Living up to Life



BIOSYSTEMS

## Safety Data Sheet Spray-Fix® Aerosol

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND THE COMPANY

#### 1.1 Product Identifier

Trade Name                      Spray-Fix Aerosol  
Product #                        3801820  
SDS #                              165  
SDS Date                         August 22, 2013

#### 1.2 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Product Use:                    Cytology fixative  
Uses Advised Against:        All other uses.

#### 1.3 Details of the Supplier of the Substance or Mixture

Manufacturer/Preparer:	Leica Biosystems Richmond, Inc. 5205 Route 12 Richmond, IL 60071 800-225-8867	Leica Biosystems Canada, Inc. 83 Terracon Place Winnipeg, Manitoba R2J 4B3 800-665-7425
------------------------	--	--

#### 1.4 Emergency Telephone Number

Emergency Spill Information    1-800- 424-9300 (CHEMTREC)  
   +1-703-527-3887 International calls (call collect)  
Other Product Information:     1-800-225-8867

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1 Classification of the Substance or Mixture

##### CLP/GHS Classification (1272/2008):

Physical:	Health:	Environmental
Aerosols Category 1	Specific Target Organ Toxicity - Single Exposure Category 1	Not Hazardous

EU Classification (67/548/EEC): F+, Xn, R12, R20/21/22, R68/20/21/22

#### 2.2 Label Elements

DANGER! Contains methanol, and hydrocarbon propellant



#### Hazard Phrases

H222	Extremely flammable aerosol
H229	Pressurized container: may burst if heated.
H370	Causes damage to nervous system and eyes.

#### Precautionary Phrases

P210	Keep away from heat/sparks/open flames/hot surfaces. – No smoking
P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: Do not pierce or burn, even after use.
P260	Do not breathe vapors.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P307 + P311	IF exposed: Call a POISON CENTER or doctor/physician.
P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
P501	Dispose of container/contents to approved disposal site in accordance with all local and national regulations.

2.3 Other Hazards: None

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substances

Chemical Name	CAS Number / EINECS Number / REACH Reg. Number	% (w/w)	EU Classification (67/548/EEC)	CLP/GHS Classification (1272/2008)
Ethanol	64-17-5 200-578-6	<80	F R11	Flammable Liquid Category 2 (H225)
Isopropanol	67-63-0 200-661-7	<5	F, Xi R11, R36, R67	Flammable Liquid Category 2 (H225) Eye Irritation Category 2A (H319) Specific Target Organ Toxicity – Single Exposure Category 3 (H336)
Methanol	67-56-1 200-659-6	<5	F, T R11, R23/24/25, R39/23/24/25	Flammable Liquid Category 2 (H225) Acute Toxicity Category 3 (H301, H311, H331) Specific Target Organ Toxicity – Single Exposure Category 1 (H370)
Hydrocarbon Propellant	68476-86-8 270-705-8	10 - 25	F+, R12	Flammable Gas Category 1 (H220)

See Section 16 for full text of GHS and EU Classifications.

### SECTION 4: FIRST AID MEASURES

#### 4.1 Description of First Aid Measures

##### First Aid

**Eye contact:** Immediately flush eye with water for at least 15 minutes while lifting the upper and lower lids.  
Get medical attention if irritation persists.

**Skin contact:** Wash thoroughly with soap and water. Get medical attention if irritation develops. Remove contaminated clothing and laundry before reuse.

**Inhalation:** Remove victim to fresh air. Get medical attention if irritation persists. If breathing is difficult have qualified individual administer oxygen and get immediate medical attention. If breathing stops, give artificial respiration and get immediate medical attention.

**Ingestion:** Unlikely route of exposure for an aerosol. Do not induce vomiting unless directed to do so by medical personnel. If the victim is conscious and alert, have them rinse their mouth with water. Never give anything by mouth to an unconscious or drowsy person. Get immediate medical attention.

**See Section 11 for more detailed information on health effects.**

**4.2 Most important symptoms and effects, both acute and delayed:** May cause eye, skin and respiratory irritation. Inhalation of vapors may cause abdominal pain and nervous system effects including dizziness, drowsiness, nausea, vomiting, visual disturbances and unconsciousness. Harmful or fatal if swallowed.

**4.3 Indication of any immediate medical attention and special treatment needed:** Immediate medical treatment is required for ingestion.

## **SECTION 5: FIREFIGHTING MEASURES**

### **5.1 Extinguishing Media:**

Use dry chemical, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>), or water spray.

### **5.2 Special Hazards Arising from the Substance or Mixture**

**Unusual Fire and Explosion Hazards:** Extremely flammable aerosol. Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back. A vapor and air mixture can create an explosion hazard in confined spaces. Flames may be invisible in daylight.

**Combustion Products:** Oxides of carbon, smoke.

**5.3 Advice for Fire-Fighters:** Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool. Use shielding to protect from bursting cans.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **6.1 Personal Precautions, Protective Equipment and Emergency Procedures:**

Wear appropriate protective equipment. Eliminate all ignition sources and ventilate the area with explosion-proof equipment. Prevent entry into basements or confined areas.

### **6.2 Environmental Precautions:**

Prevent entry in storm sewers and waterways. Report spill as required by local and federal regulations.

### **6.3 Methods and Material for Containment and Cleaning Up:**

Place leaking can in a pail in a well ventilated area away from ignition sources until pressure has dissipated. Collect liquid using non-combustible absorbents and place into a suitable container for disposal.

### **6.4 Reference to Other Sections:**

Refer to Section 8 for personal protective equipment and Section 13 for disposal information.

## SECTION 7: HANDLING and STORAGE

### 7.1 Precautions for Safe Handling:

Avoid eye and skin contact. Avoid breathing vapors. Use only with adequate ventilation. Wash thoroughly after handling. Remove contaminated clothing and launder before re-use. Keep product away from heat, sparks and all other sources of ignition. Do not spray near flames or on hot surfaces.

### 7.2 Conditions for Safe Storage, Including any Incompatibilities:

Keep product away from heat, sparks and all other sources of ignition.

Protect containers from physical damage. Store in a cool area. Keep away from excessive heat and open flames. Store away from oxidizers. Store below 120°F, and out of direct sunlight.

Do not pierce or burn, even after use. Follow all SDS precautions in handling empty containers

### 7.3 Specific end use(s):

Industrial uses: None identified

Professional uses: Cytology fixative

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control Parameters:

Chemical Name	US OEL	EU IOEL	UK OEL	Germany OEL
Ethanol	1000 ppm TWA OSHA PEL 1000 ppm STEL ACGIH TLV	None Established	1000 ppm TWA	500 ppm TWA 1000 ppm STEL
Isopropanol	400 ppm TWA OSHA PEL 200 ppm TWA, 400 ppm STEL ACGIH TLV	None Established	400 ppm TWA, 500 ppm STEL	200 ppm TWA, 400 ppm STEL
Methanol	200 ppm TWA OSHA PEL 200 ppm TWA, 250 ppm STEL skin ACGIH TLV	200 ppm TWA skin	200 ppm TWA, 250 ppm STEL	200 ppm TWA, 800 ppm STEL
Hydrocarbon Propellant	1000 ppm TWA OSHA PEL 1000 ppm TWA ACGIH TLV (as Liquefied Petroleum Gas)	None Established	1000 ppm TWA, 1250 ppm STEL	None Established

Refer to local or national authority for exposure limits not listed above.

Chemical Name	Biological Limit Value
Ethanol	None Established
Isopropanol	Acetone in urine 40 mg/L, end of shift at end of workweek (ACGIH)
Methanol	Methanol in urine 15 mg/L, end of shift (ACGIH)
Hydrocarbon Propellant	None Established

### 8.2 Exposure Controls:

**Recommended Monitoring Procedures:** Collection on charcoal tubes with analysis by gas chromatography.

**Appropriate Engineering Controls:** Use with adequate local exhaust ventilation to maintain exposure levels below the occupational exposure limits. Use explosion-proof equipment where required.

#### Personal Protective Measures

**Eye/face Protection:** Wear safety glasses.

**Skin Protection:** Impervious clothing as needed to avoid skin contact.

**Hands:** Impervious gloves (butyl or nitrile rubber) as needed to avoid skin contact.

**Respiratory Protection:** None needed with adequate ventilation. If the occupational exposure limit is exceeded, use an approved supplied air respirator. Selection of respiratory protection depends on the contaminant type, form and concentration. Select in accordance with OSHA 1910.134 or other applicable regulations and good Industrial Hygiene practice.

**Other protection:** Suitable washing facilities should be available.

## SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

### 9.1 Information on basic Physical and Chemical Properties

<b>Appearance:</b> Clear, colorless liquid in an aerosol can.	<b>Odor:</b> Alcohol odor
<b>Odor Threshold:</b> 100 ppm (Ethanol)	<b>pH:</b> Not applicable
<b>Melting/Freezing Point:</b> -112°C (-169°F) Liquid	<b>Boiling Point:</b> 78.33°C (173°F) Liquid
<b>Flash Point:</b> : 12.7°C (55 °F) (Closed Cup) Liquid	<b>Evaporation Rate:</b> Not determined
<b>Lower Flammability Limit:</b> 3% Liquid	<b>Vapor Pressure:</b> 97 mmHg @ 20°C (MeOH)
<b>Upper Flammability Limit:</b> 19% Liquid	
<b>Vapor Density(Air=1):</b> 2.07 IPA	<b>Relative Density:</b> 0.79
<b>Solubility:</b> Soluble in water	<b>Octanol/Water Partition Coefficient:</b> Not available
<b>Autoignition Temperature:</b> 422°C (793 °F) Liquid	<b>Decomposition Temperature:</b> Not established
<b>Viscosity:</b> Not established	<b>Explosive Properties:</b> Vapors may be explosive in confined areas.
	<b>Specific Gravity (H<sub>2</sub>O= 1):</b> 0.79
<b>Oxidizing Properties:</b> None	<b>Molecular Weight:</b> Mixture
<b>Molecular Formula:</b> Mixture	

**9.2 Other Information:** None available

## SECTION 10: STABILITY and REACTIVITY

**10.1 Reactivity:** This material is not reactive under normal conditions.

**10.2 Chemical Stability:** Normally stable.

**10.3 Possibility of Hazardous Reactions:** Reaction with strong oxidizers will generate heat and cause fire.

**10.4 Conditions to Avoid:** Avoid heat, sparks, flames, and all other sources of ignition.

**10.5 Incompatible Materials:** Oxidizing agents, strong acids and bases.

**10.6 Hazardous Decomposition Products:** Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: oxides of carbon.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on Toxicological Effects:

#### Potential Health Effects:

**Eye Contact:** May cause irritation with redness, tearing and swelling.

**Skin contact:** May cause irritation and dryness. Repeated exposure may cause dermatitis. May be harmful if absorbed through the skin.

- Inhalation:** May cause respiratory tract irritation and central nervous system effects such as dizziness, drowsiness, nausea, vomiting, visual disturbances and unconsciousness.
- Ingestion:** Swallowing may cause gastrointestinal effects including abdominal pain, nausea and diarrhea and central nervous system effects including dizziness, drowsiness, nausea, vomiting, visual disturbances and unconsciousness. May cause permanent blindness.

**Acute toxicity:**

Ethanol: LD50 oral rat 7060 mg/kg; LC50 inhalation rat 20000 ppm/10 hr.  
Isopropanol: LD50 oral rat 5045 mg/kg; LD50 dermal rabbit 12,800 mg/kg  
Methanol: LD50 oral rat 5628 mg/kg; LC50 inhalation rat 64000 ppm/4 hr; LD50 dermal rabbit 15,800 mg/kg  
Hydrocarbon Propellant: No data available.

**Skin corrosion/irritation:** No data available for mixture. Components are mild skin irritants.

**Eye damage/ irritation:** No data available for mixture. Isopropanol is irritating to eyes.

**Respiratory Irritation:** No data available for mixture. High concentrations may be irritating to the respiratory system.

**Respiratory Sensitization:** No data available for mixture. None of the components are respiratory sensitizers.

**Skin Sensitization:** No data available for mixture. None of the components are skin sensitizers.

**Germ Cell Mutagenicity:** No data available for mixture. Hydrocarbon Propellant is classified as a germ cell mutagen in the European Union.

**Carcinogenicity:** No data available for mixture. None of the components of this product are listed as carcinogens by OSHA, ACGIH, IARC, NTP, or the EU Dangerous Substances Directive. Ingestion of alcoholic beverages is known to cause cancer in humans (IARC group 1).

**Reproductive Toxicity:** No data available for mixture. Ethanol is known to cause developmental toxicity when intentionally ingested during pregnancy.

**Specific Target Organ Toxicity:**

Single Exposure: Methanol has been found to cause visual and nervous system damage in studies with humans and animals.

Repeat Exposure: Ethanol when consumed as a beverage has been found to cause damage to the liver, nervous system and reproductive system.

## SECTION 12: ECOLOGICAL INFORMATION

**12.1 Toxicity:**

Ethanol: LC50 rainbow trout 13000 mg/L/96 hr; LC50 daphnia magna 9268-14221 mg/L/48 hr; EC50 *Chlorella pyrenoidosa* (Green algae; growth inhibition) 9310 mg/L/48 hr  
Isopropanol: LC50 fathead minnows 11,130 mg/L/48 hr; LC50 brown shrimp 1400 mg/L/48 hr  
Methanol: LC50 fathead minnows 29,400 mg/L/96 hr; EC50 daphnia magna >10,000 mg/L/24 hr

**12.2 Persistence and degradability:** Ethanol, methanol and isopropanol are readily biodegradable in screening tests

**12.3 Bioaccumulative Potential:** Ethanol and isopropanol have an estimated BCF of 3 and methanol an estimated BCF of <10 suggesting that the potential for bioaccumulation is low.

**12.4 Mobility in Soil:** Ethanol, methanol and isopropanol are expected to have very mobility in soil.

**12.5 Results of PVT and vPvB assessment:** Not required.

12.6 Other Adverse Effects: No data available.

### SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1 Waste Treatment Methods:

Dispose in accordance with local, state and national regulations.

### SECTION 14: TRANSPORTATION INFORMATION

	14.1 UN Number	14.2 UN Proper Shipping Name	14.3 Hazard Class(s)	14.4 Packing Group	14.5 Environmental Hazards
US DOT	UN1950	Aerosols, flammable	2.1	N/A	No
Canadian TDG	UN1950	Aerosols, flammable	2.1	N/A	No
EU ADR/RID	UN1950	Aerosols, flammable	2.1	N/A	No
IMDG	UN1950	Aerosols, flammable	2.1	N/A	No
IATA/ICAO	UN1950	Aerosols, flammable	2.1	N/A	No

14.6 Special Precautions for User: None

14.7 Transport in Bulk According to Annex III MARPOL 73/78 and the IBC Code: Not determined.

### SECTION 15: REGULATORY INFORMATION

#### 15.1 Safety, Health and Environmental Regulations/Legislation Specific for the Substance or Mixture

##### INTERNATIONAL INVENTORIES

**EPA TSCA INVENTORY:** All of the components are listed on the TSCA inventory.

**CANADIAN ENVIRONMENTAL PROTECTION ACT:** All of the ingredients are listed on the Canadian Domestic Substances List.

**EUROPEAN UNION:** All of the components of this product are listed on the European Inventory of New and Existing Chemical Substances (EINECS) inventory.

**AUSTRALIA:** All of the ingredients of this product are listed on the Australian Inventory of Chemical Substances (AICS).

**CHINA:** All of the ingredients are listed on the Chinese chemical inventory.

**KOREA:** All of the components of this product are listed on the Korean Existing Chemical List (KECL).

**NEW ZEALAND:** All of the components of this product are listed on the New Zealand Inventory of Chemicals (NzIoC).

**PHILIPPINES:** All of the components of this product are listed on the Philippine Inventory of Chemicals and Chemical Substances (PICCS).

**JAPAN:** All of the components of this product are listed on the Japanese Existing and New Chemical Substances List (ENCS).

##### U.S. REGULATIONS

**OSHA HAZARD CLASSIFICATION:** Flammable, Irritant, Target Organ Effects, Compressed Gas

www.LeicaBiosystems.com

#165

**CERCLA Section 103:** The RQ for the product, based on the RQ for Methanol (5% maximum) of 5,000 lbs, is 100,000 lbs. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

**EPA SARA 302:** This product does not contain chemicals regulated under SARA Section 302.

**EPA SARA 311 HAZARD CLASSIFICATION:** Acute Health, Chronic Health, Fire Hazard, Sudden Release of Pressure.

**EPA SARA 313:** This product contains the following chemicals that are regulated under SARA Title III, section 313:  
Methanol 67-56-1 <5%

**CALIFORNIA PROPOSITION 65:** This product contains the following chemicals which are known to the State of California to cause cancer, reproductive toxicity or birth defects (developmental toxicity): Methanol <5% (Reproductive).

#### INTERNATIONAL REGULATIONS

**WHMIS CLASSIFICATION:** Class B-5, Class D-2-B

### **SECTION 16: OTHER INFORMATION**

**Revision History:** Updated Logo and website.

#### EU Classes and Risk Phrases for Reference (See Sections 2 and 3)

F+ Extremely Flammable

F Highly Flammable

T Toxic

Xi Irritant

Xn Harmful

R11 Highly Flammable

R12 Extremely Flammable

R36 Irritating to eyes.

R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.

R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed

R67 Vapours may cause drowsiness and dizziness.

R68/20/21/22 Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed

#### CLP/GHS Classification and H Phrases for Reference (See Section 3)

H220 Extremely flammable gas.

H222 Extremely flammable aerosol

H225 Highly flammable liquid and vapour.

H229 Pressurized container: may burst if heated.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H336 May cause drowsiness or dizziness.

H370 Causes damage to nervous system and eyes.

NFPA Rating:	Health: 2	Fire: 3	Instability: 0
HMIS Rating:	Health: 2	Fire: 3	Physical Hazard: 0

This Safety Data Sheet has been prepared in accordance with the REACH regulation in the EU and the Globally Harmonized System for the Classification and Labeling of Chemicals (GHS). It complies with the requirements of the Canadian Controlled Products Regulations and US 29CFR 1910.1200. To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries makes any warranty of merchantability or any other warranty, expressed or implied, which respect to such information, and we assume no liability resulting from its use. In no event shall Leica Biosystems be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages resulting from use of or reliance upon this information.

[www.LeicaBiosystems.com](http://www.LeicaBiosystems.com)

#165





