

Shotshell Ammunition

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision Date: 02/05/2015 Date of issue: 02/05/2015 Supersedes Date: 07/08/2014

Version: 1.2

SECTION 1: IDENTIFICATION

Product Identifier Product Form: Mixture

Product Name: Shotshell Ammunition (all gauges and shot types)

Synonyms: Federal Premium, Federal, Champion, Fusion, Estate, Speer LE, MSDS# F1001

Intended Use of the Product

Small Arms Ammunition

Name, Address, and Telephone of the Responsible Party

Company

Federal Cartridge Company

900 Ehlen Drive Anoka, MN 55303 T 1-800-635-7656

Emergency Telephone Number

Emergency number : 1-800-424-9300 (Inside US), 01-703-527-3887 (Outside US) - (CHEMTREC, Day or Night)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Expl. 1.4S H204 Skin Sens. 1 H317

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Warning

Hazard Statements (GHS-US)

: H204 - Fire or projection hazard

H317 - May cause an allergic skin reaction

Precautionary Statements (GHS-US): P210 - Keep away from heat, sparks, open flames, hot surfaces, - No smoking.

P234 - Keep only in original packaging.

P250 - Do not subject to friction, grinding, shock.

P261 - Avoid breathing dust, fumes.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P280 - Wear face protection, protective gloves, protective clothing. P302+P352 - IF ON SKIN: Wash with plenty of soap and water.

P321 - Specific treatment (see Section 4).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P374 - Fight fire with normal precautions from a reasonable distance.

P501 - Dispose of contents/container according to local, regional, national, and international

regulations.

Other Hazards

Other Hazards Not Contributing to the Classification: Lead and barium are toxic metals that may be released during the firing of primers. Care should be taken in the cleaning of range facilities to minimize the exposure potential to lead and barium. Persons engaged in these activities should wear protective clothing with an appropriate respirator. Range operators should consult OSHA 310.1025 for details pertaining to the handling of lead in the work environment. Severe lead intoxication has been associated in ie past with sterility, abortion, and stillbirth. Exposure to lead can aggravate pre-existing anemia, cardiovascular and respiratory

01/05/2015 EN (English US) 1/15

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

iseases and conditions related to the gastrointestinal, reproductive, renal (kidney), and central nervous systems.

Accidental Injury From Fired Cartridge: Fired ammunition can create serious injury, possibly both entrance and exit wounds. To avoid serious injury, use ammunition only in good condition and originally chambered for a particular caliber. Always keep the barrel free of any obstruction. If the gun fails to fire, a delayed firing may occur, or the gun may fire upon being opened. Keep gun muzzle pointed in a safe direction. Wait 30 seconds. Avoid exposure to breech. Carefully unload. A fired bullet has an extremely long range and can cause serious injury or death. Always be sure of the backstop, and practice safe muzzle control at all times. Avoid firing at surfaces.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>Substances</u>			
Name	Product identifier	% (w/w)	Classification (GHS-US)
Lead (as shot or slug)	(CAS No) 7439-92-1	0 - 75	Not classified
Antimony	(CAS No) 7440-36-0	0 - 5	Not classified
Copper (as shot, plating, brass or slug)	(CAS No) 7440-50-8	0 - 75	Not classified
Zinc	(CAS No) 7440-66-6	0 - 5	Not classified
Iron (as shot)	(CAS No) 1309-37-1	0 - 75	Not classified
Tungsten (as shot)	(CAS No) 12604-57-8	0 - 60	Not classified
Tin	(CAS No) 7440-31-5	0-6	Not classified
Polyethylene (as case)	(CAS No) 9002-88-4	4 – 11	Not classified
Nitrocellulose*	(CAS No) 9004-70-0	0.5 – 2	Flam. Sol. 1, H228
Nitroglycerin*	(CAS No) 55-63-0	2 - 5	Unst. Expl, H200
			Acute Tox. 2 (Oral), H300
	İ		Acute Tox. 2 (Dermal), H310
•			Acute Tox. 2 (Inhalation:dust,mist), H330
i I			STOT RE 2, H373
			Aquatic Acute 2, H401
			Aquatic Chronic 2, H411
Nickel**	(CAS No) 7440-02-0	0-6	Skin Sens. 1, H317
			Carc. 2, H351
			STOT RE 1, H372
			Aquatic Acute 1, H400
			Aquatic Chronic 3, H412
Graphite	(CAS No) 7782-42-5	≤ 0.2	Comb. Dust

^{*}The hazardous components of this product are encased within a shell and are unlikely to be released under normal handling conditions. Therefore, the health and environmental hazards associated with nitroglycerin and nitrocellulose do not apply to the product overall.

More than one of the ranges of concentration prescribed by Controlled Products Regulations has been used where neccesary due to varying composition.

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area.

Skin Contact: Wash with plenty of soap and water. If skin irritation or rash occurs: Seek medical advice.

"e Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Ingestion: Rinse mouth. Do NOT induce vomiting.

02/05/2015 EN (English US) 2/15

^{**}It is suspected that nickel causes cancer and damage to the respiratory tract via inhalation. Because this product is in massive form, it is unlikely that respiration is a potential route of exposure. Therefore, the hazards usually associated with nickel do not apply to this product.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Most Important Symptoms and Effects Both Acute and Delayed

General: May cause an allergic skin reaction. Projectiles from fired ammunition can cause puncture wounds.

Inhalation: Not expected to be a primary route of exposure.

Skin Contact: May cause an allergic skin reaction.

Eye Contact: None expected under normal conditions of use.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Fight fire with normal precautions from a reasonable distance.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Explosive. The effects are largely confined to the package and no projection of fragments of appreicable size or range is to be expected. An external fire shall not cause virtually instantaneous explosion of almost the entire contents of the package. Do not expose to heat, or ignition sources as this could cause an explosion. If heated above 200 °C (392 °F) may explode.

Reactivity: Hazardous reactions are unlikely to occur under normal circumstances.

Advice for Firefighters

Precautionary Measures Fire: Do not breathe fumes from fires or vapors from decomposition. Exercise caution when fighting any chemical fire. If product is unconfined, there is a greater risk for injury from projectiles.

Firefighting Instructions: In case of fire: Evacuate area. Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

***azardous Combustion Products: Oxides of Barium, Lead, Antimony, Aluminum, Magnesium, Nitrogen, Carbon, and Sulfur.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all unnecessary exposure.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Eliminate ignition sources.

Environmental Precautions

Avoid release to the environment.

Methods and Material for Containment and Cleaning Up

For Containment: Contain and collect as any solid. Use only non-sparking tools.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Projectiles from fired ammunition can cause puncture wounds. Avoid striking the primer of unchambered cartridges. Remove ammunition from service if any of the following conditions have occurred: corrosion, physical damage, exposure to oil or spray type lubricants.

ygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Do no eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

02/05/2015 EN (English US) 3/15

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Londitions for Safe Storage, Including Any Incompatibilities

Technical Measures: Store as defined in the Explosives Act of Canada and the provisions of the Bureau of Alcohol, Tobacco and Firearms regulations contained in 27 CFR Part 555. Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep/Store away from heat sources, ignition sources, and incompatible materials. Keep container closed when not in use.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Storage Area: Keep only in original container.

Specific End Use(s) Small Arms Ammunition

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters	ON ROIS/PERSONAL PROTEC	:10N
Nickel (7440-02-0)		
Mexico	OEL TWA (mg/m³)	1 mg/m³
USA ACGIH	ACGIH TWA (mg/m³)	1.5 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	1 mg/m³
USA NIOSH	NIOSH REL (TWA) (mg/m³)	0.015 mg/m³
USA IDLH	US IDLH (mg/m³)	10 mg/m³
Alberta	OEL TWA (mg/m³)	1.5 mg/m³
British Columbia	OEL TWA (mg/m³)	0.05 mg/m ³
Manitoba	OEL TWA (mg/m³)	1.5 mg/m ³
New Brunswick	OEL TWA (mg/m³)	1 mg/m³
Newfoundland & Labrador	OEL TWA (mg/m³)	1.5 mg/m ³
Nova Scotia	OEL TWA (mg/m³)	1.5 mg/m ³
Nunavut	OEL STEL (mg/m³)	2 mg/m ³
Nunavut	OEL TWA (mg/m³)	1 mg/m³
orthwest Territories	OEL STEL (mg/m³)	2 mg/m³
Northwest Territories	OEL TWA (mg/m³)	1 mg/m³
Ontario	OEL TWA (mg/m³)	1 mg/m³
Prince Edward Island	OEL TWA (mg/m³)	1.5 mg/m ³
Québec	VEMP (mg/m³)	1 mg/m³
Saskatchewan	OEL STEL (mg/m³)	3 mg/m ³
Saskatchewan	OEL TWA (mg/m³)	1.5 mg/m ³
Yukon	OEL STEL (mg/m³)	3 mg/m ³
Yukon	OEL TWA (mg/m³)	1 mg/m³
Lead (7439-92-1)		
Mexico	OEL TWA (mg/m³)	0.15 mg/m³
USA ACGIH	ACGIH TWA (mg/m³)	0.05 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m³)	50 μg/m³
USA NIOSH	NIOSH REL (TWA) (mg/m³)	0.050 mg/m ³
USA IDLH	US-IDLH (mg/m³)	100 mg/m³
Alberta	OEL TWA (mg/m³)	0.05 mg/m ³
British Columbia	OEL TWA (mg/m³)	0.05 mg/m ³
Manitoba	OEL TWA (mg/m³)	0.05 mg/m ³
New Brunswick	OEL TWA (mg/m³)	0.05 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m³)	0.05 mg/m ³
Nova Scotia	OEL TWA (mg/m³)	0.05 mg/m ³
Nunavut	OEL STEL (mg/m³)	0.45 mg/m³
Nunavut	OEL TWA (mg/m³)	0.15 mg/m³
'orthwest Territories	OEL STEL (mg/m³)	0.45 mg/m³
orthwest Territories	OEL TWA (mg/m³)	0.15 mg/m³
Ontario	OEL TWA (mg/m³)	0.05 mg/m³ (applies to workplaces to which the designated substances regulation does not apply)

02/05/2015 EN (English US) 4/15

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

rince Edward Island	OEL TWA (mg/m³)	0.05 mg/m ³	
Québec	VEMP (mg/m³)	0.05 mg/m³	
Saskatchewan	OEL STEL (mg/m³)	0.15 mg/m ³	
Saskatchewan	OEL TWA (mg/m³)	0.05 mg/m³	
Yukon	OEL STEL (mg/m³)	0.45 mg/m ³	
Yukon	OEL TWA (mg/m³)	0.15 mg/m ³	
Copper (7440-50-8)			
Mexico	OEL TWA (mg/m³)	1 mg/m³	
Mexico	OEL STEL (mg/m³)	2 mg/m³	
USA ACGIH	ACGIH TWA (mg/m³)	0.2 mg/m ³	
USA OSHA	OSHA PEL (TWA) (mg/m³)	1 mg/m³	
USA NIOSH	NIOSH REL (TWA) (mg/m³)	0.1 mg/m³	
USA IDLH	US IDLH (mg/m³)	100 mg/m ³	
Alberta	OEL TWA (mg/m³)	1 mg/m³	
British Columbia	OEL TWA (mg/m³)	0.2 mg/m³	
Manitoba	OEL TWA (mg/m³)	0.2 mg/m ³	
New Brunswick	OEL TWA (mg/m³)	1 mg/m³	
Newfoundland & Labrador	OEL TWA (mg/m³)	0.2 mg/m ³	
Nova Scotia	OEL TWA (mg/m³)	0.2 mg/m ³	
Nunavut	OEL STEL (mg/m³)	2 mg/m³	
Nunavut	OEL TWA (mg/m³)	1 mg/m³	
Northwest Territories	OEL STEL (mg/m³)	2 mg/m³	
Northwest Territories	OEL TWA (mg/m³)	1 mg/m³	
ntario	OEL TWA (mg/m³)	1 mg/m ³	
ince Edward Island	OEL TWA (mg/m³)	0.2 mg/m ³	
Québec	VEMP (mg/m³)	1 mg/m³	
Saskatchewan	OEL STEL (mg/m³)	3 mg/m³	
Saskatchewan	OEL TWA (mg/m³)	1 mg/m³	
Yukon	OEL STEL (mg/m³)	2 mg/m³	
Yukon	OEL TWA (mg/m³)	1 mg/m³	
Nitroglycerin (55-63-0)			
Mexico	OEL TWA (mg/m³)	0.5 mg/m ³	
Mexico	OEL TWA (ppm)	0.05 ppm	
Mexico	OEL STEL (mg/m³)	1 mg/m³	
Mexico	OEL STEL (ppm)	0.1 ppm	
USA ACGIH	ACGIH TWA (ppm)	0.05 ppm	
USA OSHA	OSHA PEL (Ceiling) (mg/m³)	2 mg/m³	
USA OSHA	OSHA PEL (Ceiling) (ppm)	0.2 ppm	
USA NIOSH	NIOSH REL (STEL) (mg/m³)	0.1 mg/m ³	
USA IDLH	US IDLH (mg/m³)	75 mg/m³	
Alberta	OEL TWA (mg/m³)	0.5 mg/m³	
Alberta	OEL TWA (ppm)	0.05 ppm	
British Columbia	OEL TWA (ppm)	0.05 ppm	
Manitoba	OEL TWA (ppm)	0.05 ppm	
New Brunswick	OEL TWA (mg/m³)	0.46 mg/m³	
New Brunswick	OEL TWA (ppm)	0.05 ppm	
Newfoundland & Labrador	OEL TWA (ppm)	0.05 ppm	
'ova Scotia	OEL TWA (ppm)	0.05 ppm	
Jnavut	OEL STEL (mg/m³)	0.46 mg/m ³	
Nunavut	OEL STEL (ppm)	0.05 ppm	
Nunavut	OEL TWA (mg/m³)	1.9 mg/m³	

02/05/2015

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	7, NO. 38 / Wioriday, Warch 20, 2012 / Rules	
unavut	OEL TWA (ppm)	0.02 ppm
Northwest Territories	OEL STEL (mg/m³)	0.46 mg/m ³
Northwest Territories	OEL STEL (ppm)	0.05 ppm
Northwest Territories	OEL TWA (mg/m³)	1.9 mg/m³
Northwest Territories	OEL TWA (ppm)	0.02 ppm
Ontario	OEL TWA (ppm)	0.05 ppm
Prince Edward Island	OEL TWA (ppm)	0.05 ppm
Québec	PLAFOND (mg/m³)	1.86 mg/m³
Québec	PLAFOND (ppm)	0.2 ppm
Saskatchewan	OEL STEL (ppm)	0.15 ppm
Saskatchewan	OEL TWA (ppm)	0.05 ppm
Yukon	OEL STEL (mg/m³)	2 mg/m³
Yukon	OEL STEL (ppm)	0.2 ppm
Yukon	OEL TWA (mg/m³)	2 mg/m³
Yukon	OEL TWA (ppm)	0.2 ppm
Graphite (7782-42-5)		
Mexico	OEL TWA (mg/m³)	2 mg/m³ (synthetic and natural)
USA ACGIH	ACGIH TWA (mg/m³)	2 mg/m³ (all forms except graphite fibers)
USA OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m³ (synthetic)
USA NIOSH	NIOSH REL (TWA) (mg/m³)	2.5 mg/m³ (natural)
USA IDLH	US IDLH (mg/m³)	1250 mg/m³
Alberta	OEL TWA (mg/m³)	2 mg/m³ (all forms except Graphite fibres)
British Columbia	OEL TWA (mg/m³)	2 mg/m³ (all forms except Graphite fibres)
1anitoba	OEL TWA (mg/m³)	2 mg/m³ (all forms except Graphite fibers)
ew Brunswick	OEL TWA (mg/m³)	2 mg/m³ (all forms except graphite fibres)
Newfoundland & Labrador	OEL TWA (mg/m³)	2 mg/m³ (all forms except Graphite fibers)
Nova Scotia	OEL TWA (mg/m³)	2 mg/m³ (all forms except Graphite fibers)
Nunavut	OEL TWA (mg/m³)	10 mg/m³ (synthetic, total mass)
Northwest Territories	OEL TWA (mg/m³)	10 mg/m³ (synthetic, total mass)
Ontario	OEL TWA (mg/m³)	2 mg/m³ (except Graphite fibres)
Prince Edward Island	OEL TWA (mg/m³)	2 mg/m³ (all forms except Graphite fibers)
Québec	VEMP (mg/m³)	2 mg/m³ (containing no Asbestos and <1% Crystalline silica,
duebee	(g/)	except Graphite fibres)
Saskatchewan	OEL STEL (mg/m³)	4 mg/m³ (natural, except Graphite fibres)
Saskatchewan	OEL TWA (mg/m³)	2 mg/m³ (natural, except Graphite fibres)
Yukon	OEL TWA (mg/m³)	10 mg/m³ (synthetic)
		To may mile to your color
Antimony (7440-36-0)	OE: THE !!-3\	05/3
Mexico	OEL TWA (mg/m³)	0.5 mg/m³
USA ACGIH	ACGIH TWA (mg/m³)	0.5 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m³)	0.5 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m³)	0.5 mg/m ³
USA IDLH	US IDLH (mg/m³)	50 mg/m ³
Alberta	OEL TWA (mg/m³)	0.5 mg/m ³
British Columbia	OEL TWA (mg/m³)	0.5 mg/m³
Manitoba	OEL TWA (mg/m³)	0.5 mg/m³
New Brunswick	OEL TWA (mg/m³)	0.5 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m³)	0.5 mg/m³
ova Scotia	OEL TWA (mg/m³)	0.5 mg/m ³
unavut	OEL STEL (mg/m³)	1.5 mg/m³
Nunavut	OEL TWA (mg/m³)	0.5 mg/m³
Northwest Territories	OEL STEL (mg/m³)	1.5 mg/m ³

02/05/2015 EN (English US) 6/15

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

orthwest Territories	OEL TWA (mg/m³)	0.5 mg/m ³
Ontario	OEL TWA (mg/m³)	0.5 mg/m ³
Prince Edward Island	OEL TWA (mg/m³)	0.5 mg/m ³
Québec	VEMP (mg/m³)	0.5 mg/m ³
Saskatchewan	OEL STEL (mg/m³)	1.5 mg/m ³
Saskatchewan	OEL TWA (mg/m³)	0.5 mg/m ³
Yukon	OEL STEL (mg/m³)	0.75 mg/m ³
Yukon	OEL TWA (mg/m³)	0.5 mg/m ³
Barium (7440-39-3)		
USA ACGIH	ACGIH TWA (mg/m³)	0.5 mg/m ³
Alberta	OEL TWA (mg/m³)	0.5 mg/m ³
British Columbia	OEL TWA (mg/m³)	0.5 mg/m ³
Manitoba	OEL TWA (mg/m³)	0.5 mg/m ³
New Brunswick	OEL TWA (mg/m³)	0.5 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m³)	0.5 mg/m ³
Nova Scotia	OEL TWA (mg/m³)	0.5 mg/m ³
Ontario	OEL TWA (mg/m³)	0.5 mg/m ³
Prince Edward Island	OEL TWA (mg/m³)	0.5 mg/m ³
Saskatchewan	OEL STEL (mg/m³)	1.5 mg/m ³
Saskatchewan	OEL TWA (mg/m³)	0.5 mg/m ³
	The state of the s	

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are bserved.

ersonal Protective Equipment: Gloves. Safety glasses.





Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: In case of projectile hazard: Safety glasses. Face shield. **Skin and Body Protection:** Wash contaminated clothing before reuse.

Respiratory Protection: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

Environmental Exposure Controls: Do not allow the product to be released into the environment.

Other Information: Do not eat, drink or smoke during use. If noise levels exceed OSHA limits while firing this product, use hearing protection in accordance with OSHA's Hearing Conservation Standard, 29 CFR 1910.95.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State : Solid

Appearance : Brass or nickel plated cup, plastic body of varying color.

Odor : Not available
Odor Threshold : Not available
pH : Not available
Relative Evaporation Rate (butylacetate=1) : Not available
Melting Point : Not available
"eezing Point : Not available

siling Point: Not availableFlash Point: Not availableAuto-ignition Temperature: Not available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Jecomposition Temperature Not available Not available Flammability (solid, gas) Not available Lower Flammable Limit Not available Upper Flammable Limit Vapor Pressure Not available Relative Vapor Density at 20 °C Not available Not available Relative Density $3.1 - 8.0 \text{ g/cm}^3$ Specific Gravity Solubility Not available Partition coefficient: n-octanol/water Not available Viscosity Not available

Explosive properties : Explosive; fire or projection hazard **Explosion Data – Sensitivity to Mechanical Impact** : Sensitive to mechanical impact

Explosion Data – Sensitivity to Static Discharge : Insensitive

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Hazardous reactions are unlikely to occur under normal circumstances.

Chemical Stability: Stable under recommended handling and storage conditions (see section 7). However, because of the design of ammunition and its components, partial detonation upon impact or intense heat may occur. Mass detonation will not occur.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Hazardous Decomposition Products: Metal oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

'nformation on Toxicological Effects - Product

. cute Toxicity: Not classified

LD50 and LC50 Data:

ED30 dila EC30 Data:		
Small Arms Ammunition – Shotshell Ammunition		
ATE US (oral)	100.00 mg/kg body weight	
ATE US (dermal)	300.00 mg/kg body weight	
ATE US (dust, mist)	0.50 mg/l/4h	

Skin Corrosion/Irritation: Not classified
Serious Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not classified

Carcinogenicity: Reasonably anticipated to be human carcinogen.

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Not expected to be a primary route of exposure.

Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: None expected under normal conditions of use.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

<u>Information on Toxicological Effects - Ingredient(s)</u>

LD50 and LC50 Data:

nc oxide (1314-13-2)	
່ ມ50 Oral Rat	> 5000 mg/kg
ATE US (dust, mist)	5.80 mg/l/4h

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

lickel (7440-02-0)		
LD50 Oral Rat	> 9000 mg/kg	
Nitroglycerin (55-63-0)		
LD50 Oral Rat	105 mg/kg	
LD50 Dermal Rabbit	> 280 mg/kg	
ATE US (dust, mist)	0.05 mg/l/4h	
Graphite (7782-42-5)		
LD50 Oral Rat	> 2000 mg/kg	
Antimony (7440-36-0)		
LD50 Oral Rat	100 mg/kg	
Barium (7440-39-3)		
LD50 Oral Rat	132 mg/kg	
Nickel (7440-02-0)		
IARC Group	2B	
National Toxicity Program (NTP) Status	Reasonably anticipated to be Human Carcinogen.	
Lead (7439-92-1)		
IARC Group	2A	
National Toxicity Program (NTP) Status	Reasonably anticipated to be Human Carcinogen.	

SECTION 12: ECOLOGICAL INFORMATION

Toxicity Not classified	
Zinc oxide (1314-13-2)	
LC50 Fish 1	780 μg/l Species: Pimephales promelas
DEC chronic fish	0.026 mg/l Species: Jordanella floridae
Nickel (7440-02-0)	
LC50 Fish 1	100 mg/l (Exposure time: 96 h - Species: Brachydanio rerio)
EC50 Daphnia 1	100 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	1.3 mg/l (Exposure time: 96 h - Species: Cyprinus carpio (semi-static))
EC50 Daphnia 2	1 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 Other Aquatic Organisms 2	0.174 - 0.311 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata [static])
Zinc (7440-66-6)	
LC50 Fish 1	2.16 - 3.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	0.139 - 0.908 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC 50 Fish 2	0.211 - 0.269 mg/l (Exposure time: 96 h - Species: Pimephales promelas [semi-static])
Lead (7439-92-1)	
LC50 Fish 1	0.44 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static])
ECSO Daphnia 1	600 μg/l (Exposure time: 48 h - Species: water flea)
LC 50 Fish 2	1.17 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
Copper (7440-50-8)	
LC50 Fish 1	≤ 0.0068 (0.0068 - 0.0156) mg/l (Exposure time: 96 h - Species: Pimephales promelas)
EC50 Daphnia 1	0.03 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 Other Aquatic Organisms 1	0.043 - 0.054 mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata [static])
LC 50 Fish 2	0.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Other Aquatic Organisms 2	0.031 - 0.054 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata [static])
Nitroglycerin (55-63-0)	
LC50 Fish 1	0.87 - 3.25 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])
^50 Daphnia 1	46 - 55 mg/l (Exposure time: 48 h - Species: Daphnia magna)
50 Fish 2	0.87 - 2.21 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus (static))
EC50 Daphnia 2	38 - 55 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

02/05/2015 EN (English US) 9/15

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Persistence and Degradability

2 CIDISCHICE CHIC POST COCCUPY	
Small Arms Ammunition – Shotshell Ammunition	
Persistence and Degradability Not established.	
Copper (7440-50-8)	
Persistence and Degradability Not readily biodegradable.	

Bioaccumulative Potential

Small Arms Ammunition – Shotshell Ammunition	
Bioaccumulative Potential	Not established.

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Ecology - Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT

Proper Shipping Name : CARTRIDGES, SMALL ARMS

Hazard Class : 1.4S
Identification Number : UN0012
Label Codes : 1.4S
Packing Group : II
ERG Number : 114



4.1.1 Domestic Ground packaged per 49CFR173.63

∠roper Shipping Name : None

Hazard Class : Limited Quantity

Identification Number: NoneLabel Codes: NonePacking Group: None



14.2 In Accordance with IMDG

Proper Shipping Name : CARTRIDGES, SMALL ARMS

Hazard Class : 1.4S
Identification Number : UN0012
Label Codes : 1.4S
EmS-No. (Fire) : F-B
EmS-No. (Spillage) : S-X



14.3 In Accordance with IATA

Proper Shipping Name : CARTRIDGES, SMALL ARMS

Identification Number: UN0012Hazard Class: 1Label Codes: 1.4SERG Code (IATA): 3L



14.4 In Accordance with TDG

Proper Shipping Name : CARTRIDGES, SMALL ARMS

Packing Group : II
Hazard Class : 1.45
Identification Number : UN0012
Label Codes : 1.45



r 49CFR173.63(b): Limited quantities of Cartridges, small arms, Cartridges, power device, Cartridges for tools, blank, and Cases, cartridge, empty with primer. (1)(i) Cartridges, small arms, Cartridges, power device (used to project fastening devices), Cartridges for tools, blank, and Cases, cartridge, empty with primer that have been classed as Division 1.4S explosive may be offered for transportation and transported as limited quantities when packaged in accordance with paragraph (b)(2) of this section. Packages

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

containing such articles may be marked with either the marking prescribed in §172.315(a) or (b) of this subchapter and offered for transportation and transported by any mode. For transportation by aircraft, the package must conform to the applicable requirements of §173.27 of this part. In addition, packages containing such articles offered for transportation by aircraft must be marked with the proper shipping name as prescribed in the §172.101 Hazardous Materials Table of this subchapter. Packages containing such articles are not subject to the shipping paper requirements of subpart C of part 172 of this subchapter unless the material meets the definition of a hazardous substance, hazardous waste, marine pollutant, or is offered for transportation and transported by aircraft or vessel. Additionally, packages containing such articles are excepted from the requirements of subparts E (Labeling) and F (Placarding) of part 172 of this subchapter.

CTION 15: REGULATORY INFORMATION		
S Federal Regulations		
Small Arms Ammunition – Shotshell Ammunition		
ARA Section 311/312 Hazard Classes	Immediate (acute) health hazard	
	Delayed (chronic) health hazard	
	Sudden release of pressure hazard	
ickel (7440-02-0)		
sted on the United States TSCA (Toxic Substances Control Act)	inventory	
sted on SARA Section 313 (Specific toxic chemical listings)		
Q (Reportable Quantity, Section 304 of EPA's List of Lists):	100 lb (only applicable if particles are < 100 μm)	
ARA Section 313 - Emission Reporting	0.1 %	
nc (7440-66-6)		
sted on the United States TSCA (Toxic Substances Control Act)	inventory	
sted on SARA Section 313 (Specific toxic chemical listings)		
ARA Section 313 - Emission Reporting	1.0 % (dust or fume only)	
trocellulose (9004-70-0)		
sted on the United States TSCA (Toxic Substances Control Act)	inventory	
ad (7439-92-1)		
sted on the United States TSCA (Toxic Substances Control Act)	inventory	
sted on SARA Section 313 (Specific toxic chemical listings)		
RA Section 313 - Emission Reporting	0.1 %	
Copper (7440-50-8)		
ited on the United States TSCA (Toxic Substances Control Act)	inventory	
sted on SARA Section 313 (Specific toxic chemical listings)		
RA Section 313 - Emission Reporting	1.0 %	
Nitroglycerin (55-63-0)		
ted on the United States TSCA (Toxic Substances Control Act)	inventory	
ted on SARA Section 313 (Specific toxic chemical listings)	·	
RA Section 313 - Emission Reporting	1.0 %	
aphite (7782-42-5)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Antimony (7440-36-0)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Listed on SARA Section 313 (Specific toxic chemical listings)		
SARA Section 313 - Emission Reporting 1.0 %		
Barium (7440-39-3)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
sted on SARA Section 313 (Specific toxic chemical listings)		
RA Section 313 - Emission Reporting	1.0 %	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

JS	State	Regul	lations
-	Jiaic	NEEU	ialiulia

Nickel (7440-02-0)	
U.S California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the
	State of California to cause cancer.
Lead (7439-92-1)	
U.S California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the
	State of California to cause cancer.
U.S California - Proposition 65 - Developmental Toxicity	WARNING: This product contains chemicals known to the
	State of California to cause birth defects.
U.S California - Proposition 65 - Reproductive Toxicity - Female	WARNING: This product contains chemicals known to the
	State of California to cause (Female) reproductive harm.
U.S California - Proposition 65 - Reproductive Toxicity - Male	WARNING: This product contains chemicals known to the
	State of California to cause (Male) reproductive harm.

Nickel (7440-02-0)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) Special Hazardous Substances
- U.S. Pennsylvania RTK (Right to Know) List

Zinc (7440-66-6)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- 'I.S. Pennsylvania RTK (Right to Know) List

.itrocellulose (9004-70-0)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Lead (7439-92-1)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Copper (7440-50-8)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Nitroglycerin (55-63-0)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Graphite (7782-42-5)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

ntimony (7440-36-0)

- J.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List

02/05/2015

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

J.S. - Pennsylvania - RTK (Right to Know) List

Barium (7440-39-3)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Canadian Regulations

Small Arms Ammunition - Centerfire Rifle & Pistol Ammunition

WHMIS Classification

Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Class F - Dangerously Reactive Material

Note: Explosives are not regulated under WHMIS. They are subject to the regulations of the

Explosives Act of Canada.





Lead, dihydroxy[2,4,6-trinitro-1,3-benzenediolato(2-)]di-(12403-82-6)

Listed on Non-Domestic Substances List (NDSL)

Nickel (7440-02-0)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Listed on the Canadian Ingredient Disclosure List

IDL Concentration 0.1 %

JHMIS Classification Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Zinc (7440-66-6)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification Class B Division 6 - Reactive Flammable Material

Nitrocellulose (9004-70-0)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification Class B Division 4 - Flammable Solid

Class F - Dangerously Reactive Material

Lead (7439-92-1)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Listed on the Canadian Ingredient Disclosure List

IDL Concentration 0.1 %

WHMIS Classification Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

Copper (7440-50-8)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Listed on the Canadian Ingredient Disclosure List

IDL Concentration 1 %

WHMIS Classification Uncontrolled product according to WHMIS classification criteria

Nitroglycerin (55-63-0)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Graphite (7782-42-5)

'isted on the Canadian DSL (Domestic Substances List) inventory.

HMIS Classification Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

Antimony (7440-36-0)

Listed on the Canadian DSL (Domestic Substances List) inventory.

02/05/2015 EN (English US) 13/15

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Listed on the Canadian Ingredient Disclosure List				
IDL Concentration 1 %	·			
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria			
Barium (7440-39-3)				
Listed on the Canadian DSL	(Domestic Substances List) inventory.			
WHMIS Classification	Class B Division 6 - Reactive Flammable Material			
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects			
1-Tetrazene-1-carboximídic acid, 4-(aminoíminomethyl)-, 2-nitrosohydrazide (109-27-3)				
Listed on Non-Domestic Substances List (NDSL)				

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision date

: 02/05/2015

Other Information

: This document has been prepared in accordance with the SDS requirements of the OSHA

Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 2 (Dermal)	Acute toxicity (dermal) Category 2
Acute Tox. 2 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 2
Acute Tox. 2 (Oral)	Acute toxicity (oral) Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Carc. 2	Carcinogenicity Category 2
Comb. Dust	Combustible Dust
Expl. 1.1	Explosive Category 1.1
Expl. 1.4	Explosive Category 1.4
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Sol. 1	Flammable solids Category 1
Repr. 1A	Reproductive toxicity Category 1A
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
Unst. Expl	Unstable explosives
Water-react. 2	Substances and mixtures which in contact with water emit flammable gases Category 2
H200	Unstable explosives
H201	Explosive; mass explosion hazard
H204	Fire or projection hazard
H228	Flammable solid
Comb. Dust	May form combustible dust concentrations in air

02/05/2015 EN (English US) 14/15

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

T	
H261	In contact with water releases flammable gases
H300	Fatal if swallowed
H301	Toxic if swallowed
H302	Harmful if swallowed
H310	Fatal in contact with skin
H311	Toxic in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H330	Fatal if inhaled
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H360	May damage fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Party Responsible for the Preparation of This Document

Federal Cartridge Company 900 Ehlen Drive Anoka, MN 55303 1-800-635-7656

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS 2