

Valvoline® HIGH PERFORMANCE SAE 75W-90 GEAR OIL

® Registered Trademark, Ashland or its subsidiaries VV820

**1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

Ashland	Regulatory Information Number	1-800-325-3751
P.O. Box 2219	Telephone	614-790-3333
Columbus, OH 43216	Emergency telephone	1-800-ASHLAND (1-800-274-5263)
Product name	Valvoline® HIGH PERFORMANCE SAE 75W-90 GEAR OIL	
	® Registered Trademark, Ashland or its subsidiaries	
Product code	VV820	
Product Use Description	No data	

**2. HAZARDS IDENTIFICATION**

**Emergency Overview**

Appearance: liquid

**CAUTION!** PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION.

**Potential Health Effects**

**Exposure routes**

Inhalation, Skin contact, Eye Contact, Ingestion

**Eye contact**

Unlikely to cause eye irritation or injury.

**Skin contact**

Unlikely to cause skin irritation or injury. Prolonged or repeated contact may dry and crack the skin.

**Ingestion**

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Valvoline® HIGH PERFORMANCE SAE 75W-90 GEAR OIL

® Registered Trademark, Ashland or its subsidiaries VV820

**Inhalation**

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful.

**Aggravated Medical Condition**

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions)

**Symptoms**

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways)

**Target Organs**

No data

**Carcinogenicity**

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA).

**Reproductive hazard**

There are no data available for assessing risk to the fetus from maternal exposure to this material.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

<b>Hazardous Components</b>	<b>CAS-No.</b>	<b>Concentration</b>
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC		>=30-<40%

**4. FIRST AID MEASURES**

Valvoline® HIGH PERFORMANCE SAE 75W-90 GEAR OIL

® Registered Trademark, Ashland or its subsidiaries VV820

**Eyes**

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

**Skin**

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

**Ingestion**

First aid is not normally required. If symptoms develop, seek medical attention.

**Inhalation**

First aid is not normally required. If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention.

**Notes to physician**

**Hazards:** Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

**Treatment:** No information available.

**5. FIRE-FIGHTING MEASURES**

**Suitable extinguishing media**

regular foam (such as AFFF), Water mist, Dry powder, Carbon dioxide (CO2)

**Hazardous combustion products**

carbon dioxide and carbon monoxide, hydrogen sulfide, nitrogen oxides (NOx), Oxides of phosphorus, sulfur oxides, various hydrocarbons

**Precautions for fire-fighting**

Valvoline® HIGH PERFORMANCE SAE 75W-90 GEAR OIL

® Registered Trademark, Ashland or its subsidiaries VV820

Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Dense smoke may be generated while burning. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid.

### **NFPA Flammable and Combustible Liquids Classification**

Combustible Liquid Class IIIB

## **6. ACCIDENTAL RELEASE MEASURES**

### **Personal precautions**

No data

### **Environmental precautions**

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

### **Methods for cleaning up**

Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source, dike area of spill to prevent spreading, pump liquid to salvage tank. Remaining liquid may be taken up on sand, clay, earth, floor absorbent, or other absorbent material and shoveled into containers. Absorb liquid on vermiculite, floor absorbent or other absorbent material.

## **7. HANDLING AND STORAGE**

### **Handling**

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Avoid prolonged or repeated contact. Do not store near high heat or open flames.

### **Storage**

Keep containers closed when not in use.

## **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

### **Exposure Guidelines**

Valvoline® HIGH PERFORMANCE SAE 75W-90 GEAR OIL

® Registered Trademark, Ashland or its subsidiaries VV820

### General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

### Exposure controls

General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

### Eye protection

Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

### Skin and body protection

Not normally required. However, wear resistant gloves such as nitrile rubber to prevent irritation which may result from prolonged or repeated skin contact with product. Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

### Respiratory protection

Respiratory protection is not required under normal conditions of use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state</b>	liquid
<b>Form</b>	no data available
<b>Colour</b>	no data available
<b>Odour</b>	no data available
<b>Boiling point/boiling range</b>	392 °F / 200 °C @ 1,013.33 hPa Calculated Phase Transition Liquid/Gas
<b>Melting point/range</b>	no data available
<b>Sublimation point</b>	no data available

Valvoline® HIGH PERFORMANCE SAE 75W-90 GEAR OIL

® Registered Trademark, Ashland or its subsidiaries VV820

<b>pH</b>	no data available
<b>Flash point</b>	(>)199.00 °C Cleveland open cup
<b>Ignition temperature</b>	no data available
<b>Evaporation rate</b>	no data available
<b>Lower explosion limit/Upper explosion limit</b>	1 %(V) / 6 %(V)
<b>Particle size</b>	no data available
<b>Vapour pressure</b>	0.133 hPa @ 68 °F / 20 °C Calculated Vapor Pressure
<b>Relative vapour density</b>	no data available
<b>Density</b>	0.8613 g/cm <sup>3</sup> @ 60.01 °F / 15.56 °C
<b>Bulk density</b>	No data
<b>Water solubility</b>	no data available
<b>Solubility</b>	no data available
<b>Partition coefficient: n-octanol/water</b>	no data available
<b>log Pow</b>	no data available
<b>Autoignition temperature</b>	no data available
<b>Viscosity, dynamic</b>	no data available
<b>Viscosity, kinematic</b>	no data available
<b>Solids in Solution</b>	no data available
<b>Decomposition temperature</b>	no data available
<b>Burning number</b>	no data available
<b>Dust explosion constant</b>	no data available
<b>Minimum ignition energy</b>	no data available

## 10. STABILITY AND REACTIVITY

### Stability

Stable.

### Conditions to avoid

None known.

### Incompatible products

Avoid contact with:, strong oxidizing agents

### Hazardous decomposition products

carbon dioxide and carbon monoxide, nitrogen oxides, Oxides of phosphorus, Sulphur oxides, various hydrocarbons

Valvoline® HIGH PERFORMANCE SAE 75W-90 GEAR OIL

® Registered Trademark, Ashland or its subsidiaries VV820

**Hazardous reactions**

Product will not undergo hazardous polymerization.

**Thermal decomposition**

No data

**11. TOXICOLOGICAL INFORMATION**

**Acute oral toxicity**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC : LD 50 Rat: > 15 g/kg

**Acute inhalation toxicity**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC : no data available

**Acute dermal toxicity**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC : LD 50 Rabbit: > 5 g/kg

**12. ECOLOGICAL INFORMATION**

**Biodegradability**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC : no data available

**Bioaccumulation**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC : no data available

**Ecotoxicity effects**

**Toxicity to fish**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC : no data available

**Toxicity to daphnia and other aquatic invertebrates.**

Valvoline® HIGH PERFORMANCE SAE 75W-90 GEAR OIL

® Registered Trademark, Ashland or its subsidiaries VV820

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC : no data available

**Toxicity to algae**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC : no data available

**Toxicity to bacteria**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC : no data available

**Biochemical Oxygen Demand (BOD)**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC : no data available

**Chemical Oxygen Demand (COD)**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC : no data available

**Additional ecological information**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC : no data available

**13. DISPOSAL CONSIDERATIONS**

**Waste disposal methods**

Dispose of in accordance with all applicable local, state and federal regulations. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

**14. TRANSPORT INFORMATION**

**REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT /LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	-----------------------------

**MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES**

Valvoline® HIGH PERFORMANCE SAE 75W-90 GEAR OIL  
® Registered Trademark, Ashland or its subsidiaries VV820

Not dangerous goods

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**

Not dangerous goods

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

Not dangerous goods

**INTERNATIONAL MARITIME DANGEROUS GOODS**

Not dangerous goods

**TRANSPORT CANADA - INLAND WATERWAYS**

Not dangerous goods

**TRANSPORT CANADA - RAIL**

Not dangerous goods

**TRANSPORT CANADA - ROAD**

Not dangerous goods

**U.S. DOT - INLAND WATERWAYS**

Not dangerous goods

**U.S. DOT - RAIL**

Not dangerous goods

**U.S. DOT - ROAD**

Not dangerous goods

\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

**15. REGULATORY INFORMATION**

**California Prop. 65**

Valvoline® HIGH PERFORMANCE SAE 75W-90 GEAR OIL

® Registered Trademark, Ashland or its subsidiaries VV820

Proposition 65 warnings are not required for this product based on the results of a risk assessment.	
--	--

**SARA Hazard Classification**

No SARA Hazards

**New Jersey RTK Label Information**

POLYMER	68037-01-4
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC VISCOSITY MODIFIER LUBRICANT ADDITIVE	
DI-TERT-BUTYL POLYSULFIDE	68937-96-2

**Pennsylvania RTK Label Information**

POLYMER	68037-01-4
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC VISCOSITY MODIFIER LUBRICANT ADDITIVE	

**Notification status**

EU. EINECS	y (positive listing)
US. Toxic Substances Control Act	y (positive listing)
Australia. Industrial Chemical (Notification and Assessment) Act	y (positive listing)
Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133)	y (positive listing)
Japan. Kashin-Hou Law List	y (positive listing)
Korea. Toxic Chemical Control Law (TCCL) List	y (positive listing)
Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act	y (positive listing)
China. Inventory of Existing Chemical Substances	y (positive listing)
New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand	n (Negative listing)

	HMIS	NFPA
Health	1	1

Valvoline® HIGH PERFORMANCE SAE 75W-90 GEAR OIL

® Registered Trademark, Ashland or its subsidiaries VV820

Flammability	1	1
Physical hazards	0	
Instability		0
Specific Hazard	--	--

**16. OTHER INFORMATION**

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).